

SECURITY INFORMATION

~~CONFIDENTIAL~~

Copy

RM L53I17a

200

NACA RM L53I17a



NACA

RESEARCH MEMORANDUM

RECENT INFORMATION ON FLAP AND TIP CONTROLS

By Douglas R. Lord and K. R. Czarnecki

Langley Aeronautical Laboratory
Langley Field, Va.

UNCLASSIFIED

NASA Tech Rep Announcement #27

1 Sept. 60

NK

14 Feb. 61 CLASSIFIED DOCUMENT

This material contains information affecting the National Defense of the United States within the meaning of the espionage laws, Title 18, U.S.C., Secs. 793 and 794, the transmission or revelation of which in any manner to an unauthorized person is prohibited by law.

NATIONAL ADVISORY COMMITTEE
FOR AERONAUTICS

WASHINGTON

November 17, 1953

~~CONFIDENTIAL~~

1B

NACA RM L53117a

~~CONFIDENTIAL~~

TECH LIBRARY KAFB, NM



0144293

NATIONAL ADVISORY COMMITTEE FOR AERONAUTICS

RESEARCH MEMORANDUM

RECENT INFORMATION ON FLAP AND TIP CONTROLS

By Douglas R. Lord and K. R. Czarnecki

INTRODUCTION

In the past few years, research programs on controls have been expanded to include systematic transonic and supersonic investigations of new types of control devices and to adapt the controls developed through subsonic research to the supersonic regime. The results now available are sufficiently extensive to warrant an evaluation of the progress to date and to establish certain trends. The data presented in the present paper are used to outline these trends rather than to give a completely comprehensive summary of the available data. A bibliography of references, however, is included.

SYMBOLS

M	stream Mach number
q	stream dynamic pressure
p	stream static pressure
p_l	local surface pressure
P	pressure coefficient, $\frac{p_l - p}{q}$
x	chordwise distance from wing-section leading edge
c	wing chord
c_T	total control chord
c_f	control chord behind hinge line
\bar{c}	wing mean aerodynamic chord

~~CONFIDENTIAL~~

2

~~CONFIDENTIAL~~

NACA RM L53I17a

\bar{c}_c	control mean aerodynamic chord
$b/2$	wing semispan
S	semispan-wing area
S_T	total control area
S_b	control area ahead of hinge line
Q	moment of control area behind hinge line about hinge line
α	wing angle of attack
δ	control deflection relative to wing
L	semispan-wing lift
L'	semispan-wing rolling moment
M'	semispan-wing pitching moment about 50-percent station of wing mean aerodynamic chord
H	control hinge moment about hinge line
C_L	lift coefficient, L/qS
C_l	rolling-moment coefficient, $L'/q2Sb$
C_m	pitching-moment coefficient, $M'/qS\bar{c}$
C_h	control hinge-moment coefficient, defined as $H/q2Q$ for flap controls and $H/qS_T\bar{c}_c$ for tip controls

Slope parameters:

$$C_{L_\delta} = \frac{\partial C_L}{\partial \delta}$$

$$C_{l_\delta} = \frac{\partial C_l}{\partial \delta}$$

$$C_{m_\delta} = \frac{\partial C_m}{\partial \delta}$$

~~CONFIDENTIAL~~

~~CONFIDENTIAL~~

$$C_{h\delta} = \frac{\partial C_h}{\partial \delta}$$

$$C_{h\alpha} = \frac{\partial C_h}{\partial \alpha}$$

All slopes were obtained at $\alpha = 0^\circ$ and $\delta = 0^\circ$.

DISCUSSION

The fundamental requirement of a control, at any speed, is that it produce the necessary lift, pitching moment, or rolling moment to control the aircraft in flight. Considerable testing of controls at high speeds has shown that the desired effectiveness can usually be obtained without difficulty. Since the supersonic theory for predicting control effectiveness is cumbersome and the assumptions are often not well-supported by experiment, simpler methods of estimating the control effectiveness are desired. It is to be expected that, to a first order, the lift of a control is directly related to the area of the control, and the moment of the control forces about a given axis is directly related to the moment of the control area about that axis. This simple concept is substantiated by data presented in figures 1 and 2 which show the results of tests in the Langley 4- by 4-foot supersonic pressure tunnel at Mach number 1.61 of a delta wing and of a trapezoidal wing. In these figures, the slopes of the curves of lift, rolling-moment, and pitching-moment coefficients with control deflection are plotted as functions of the control area, control-area moment about the roll center, and control-area moment about the pitch center, respectively, for the control configurations tested. It is evident that to a first order it is possible to estimate from these correlations the effectiveness of any control on the wings shown, regardless of control plan form. Similar results have been obtained for wings of other plan forms (refs. 1 to 3). Some flight results (ref. 4) indicate that correlations may not be obtainable for some controls on high-aspect-ratio, highly swept wings.

In view of the fact that satisfactory control effectiveness can be obtained and usually can be estimated, a primary objective of research on controls at the present time is to develop methods for balancing the forces acting on the controls to improve the hinge-moment characteristics. In order to reduce the magnitude of the control hinge moments, several methods have been used, such as overhang nose balances, horn balances,

~~CONFIDENTIAL~~

~~CONFIDENTIAL~~

NACA RM L53I17a

tip controls; all-movable wings, tabs, and paddle balances. Until recently, very few data have been available on overhang balances at high speeds; however, recent transonic and supersonic tests of trailing-edge controls having various amounts of overhang nose balance have been made on the transonic bump in the Langley high-speed 7- by 10-foot tunnel and in the Langley 9- by 12-inch supersonic blowdown tunnel. Figure 3 shows the variation with Mach number of the hinge-moment-parameter slopes with control deflection and with angle of attack for the two extreme test configurations, one having no overhang balance and the other having 100-percent balance. Data for the configurations having a balance area between 0 and 100 percent fall between the curves shown. Throughout this paper, percent balance is defined as the ratio of control area ahead of the hinge line to control area behind the hinge line, expressed as a percentage. For this type of control, the hinge-moment-coefficient slopes, which are based on the moment of the control area behind the hinge line, have been converted to hinge-moment-parameter slopes, which are based on the moment of the total control area about the control leading edge, in order to make the data for the two controls directly comparable. It should be noted that all the tests were made with a rounded leading edge on the control and that the 9- by 12-inch-tunnel data were obtained on a wing mounted on a half-body, which may explain some of the discrepancies in the data from the two tests. In general, the data indicate that the nose balance is effective in changing the hinge moment due to control deflection throughout the speed range tested. The nose balance causes a much larger change in hinge moment due to wing angle of attack at supersonic speeds than at subsonic speeds. Since these slopes were obtained at a control deflection of 0° and an angle of attack of 0° , it appears that, in order to gain more insight into the effectiveness of the nose balance at subsonic and supersonic speeds, it will be necessary to consider the effect of control deflection and angle of attack.

Figure 4 shows for a Mach number of 0.60 and a Mach number of 1.96 the variation of the hinge-moment parameter with control deflection at an angle of attack of 0° and with angle of attack at a control deflection of 0° for the two control configurations discussed in the previous figure. In both the subsonic and supersonic cases, the unbalanced control, as designated by the solid curves, has fairly linear characteristics and for the Mach numbers shown there is only a small change in slope due to Mach number of the hinge-moment curve with control deflection near $\delta = 0^\circ$. For the 100-percent-balanced control, the subsonic curve shows a large balancing effect with increasing control deflection at the small deflections. At supersonic speed, the 100-percent-balanced control shows less balancing action than it did at subsonic speed. Other data at angles of attack have shown that at supersonic speeds the balance is ineffective at positive control deflections when the nose of the control lies in the dead-air region behind the wing but has a strong balancing effect at negative control deflections when the control nose is

~~CONFIDENTIAL~~

exposed. At all the test angles of attack, the effect of the nose balance is less at subsonic than at supersonic speed when the control deflection is 0° .

Since at supersonic speeds the dead-air region from the wing seems to be important, it would appear that changes in wing section to minimize this region would improve the balancing effectiveness of this type of control. The results of two-dimensional tests in the Langley 9-inch supersonic tunnel at a Mach number of 2.40, in which changes in section were made, are shown in figure 5. The hinge-moment-parameter slopes, which were taken from fairly linear curves, are plotted as functions of the ratio of control balancing area to total control area. Models were tested for two of the sections with different balance-area ratios as shown by the curves. Models of all four sections for a balance-area ratio of 0.375 were tested. For these tests an area ratio of approximately 0.6 would be required to balance the hinge moment due to control deflection for the basic configuration (denoted by the solid curve); whereas a ratio of 0.4 is all that is required to balance the hinge moment due to angle of attack. The changes in section had only a minor effect on the hinge moment due to control deflection, contrary to what might have been expected, and had considerable effect on the hinge moment due to angle of attack.

In figure 6, pressure distributions are presented for a typical section modification, in this case wing bevel, to illustrate this phenomenon in more detail. The solid curves indicate the pressure variation along the chord on the upper surface and the dashed curves show the pressure variation on the lower surface. The left-hand side of the figure shows the effect of a change in section on the pressure distributions due to a large control deflection at an angle of attack of 2° . In this case, beveling the wing ahead of the control increased the load on the balancing portion of the control, but it also increased the load on the control behind the hinge line so that the net effect on the hinge moment was negligible.

The right-hand side of the figure shows the effect of a change in section on the pressure distribution due to an angle of attack of 8° with a control deflection of 0° . In this case, there is little change on the upper surface; however, the lower-surface peak-pressure point moves forward and increases in intensity. Behind the hinge line there is some forward shift in the center of pressure of the load. The resultant hinge moment is therefore much more positive because of the modification of the wing section. Another way of increasing the balancing action of the overhang-nose-balance control is to increase the gap between the wing and the control so that the control behaves more like an isolated wing. However, such a modification results in a drag penalty, as do the modifications to the wing section.

~~CONFIDENTIAL~~

~~CONFIDENTIAL~~

A second method for reducing the hinge moments obtained on trailing-edge controls at supersonic speeds is to add a horn balance, ahead of the hinge line, to the outboard portion of the control. Figure 7 shows a correlation of hinge-moment-slope parameters at $M = 1.60$ obtained from recent tests of horn-balanced controls in the Ames 6- by 6-foot supersonic tunnel (ref. 5), tests in the C.I.T. Jet Propulsion Laboratory 12-inch supersonic tunnel (refs. 6, 9, and 16), and on a Langley Pilotless Aircraft Research Division rocket research model (refs. 17 and 18). The correlation with the ratio of control-balance area to total control area is approximately linear, even though both triangular horns and rectangular horns are included on delta wings having leading-edge sweeps from 60° to 75° . As compared to the overhang nose balance, the balancing horns are considerably more effective in reducing the hinge moments due to control deflection and angle of attack. A horn of only one-third the control area balances $C_{h\delta}$ and a horn of only 15 percent of the control area balances $C_{h\alpha}$ for this Mach number condition. With this type of control, it is of course impossible to balance both $C_{h\delta}$ and $C_{h\alpha}$ closely with one balance configuration.

Still another method of reducing the control hinge moments at supersonic speeds is to use tip controls, in which the hinge-line location may be chosen to balance the forces acting on the control. Figure 8 presents recent data on 60° half-delta tip controls on a 60° delta wing from Langley Pilotless Aircraft Research Division rocket tests (ref. 28) and tests in the Langley 9- by 12-inch supersonic blowdown tunnel (refs. 29 and 30), the Langley 4- by 4-foot supersonic pressure tunnel (ref. 13), the Langley 9- by 9-inch Mach number 4 blowdown jet, and the Langley 11-inch hypersonic tunnel. These data extend the speed range for which tip-control data were previously available to the hypersonic region and increase the range of balances tested. For comparative purposes, experimental curves are also shown for the hinge-moment-slope parameters of a 30-percent-chord trailing-edge control obtained from two-dimensional tests in some of the same test facilities (refs. 20 to 22). In general, the hinge-moment-slope parameters for the tip controls vary with shifts in the hinge-line location in a systematic manner, as would be expected. The linear-theory curve is shown for the 55-percent-balance condition, which corresponds to the square test points of the experimental data.

In view of the interest shown in data at the highest available Mach number, figure 9 shows in more detail the hinge-moment characteristics with control deflection and angle of attack for the two types of controls tested at a Mach number of 6.90. The hinge-moment-coefficient scales are different for the two controls and the characteristics are not directly comparable because of the differences in moment areas on which the coefficients are based. The linear-theory curves are shown for the range of test angles, although the linear theory is obviously invalid at this Mach number except for very small angles and extremely thin wings.

~~CONFIDENTIAL~~

~~CONFIDENTIAL~~

The shock-expansion theory gives a reasonable prediction of the hinge-moment-coefficient variation with control deflection for the trailing-edge control and gives excellent prediction of the variation of hinge-moment coefficient with angle of attack. For the tip control, the shock-expansion theory, computed by assuming that the flow over the control was completely two-dimensional, provided an excellent prediction of the hinge-moment characteristics at the small angles. The linear-theory agreement with the shock-expansion theory at the small angles is fortuitous as a result of the section of the particular control tested.

The agreement between shock-expansion theory and experiment for the control hinge-moment coefficient due to control deflection, shown in this figure, tends to give an overly optimistic impression of our ability to predict the flow characteristics at this Mach number. Figure 10 shows the experimental and shock-expansion pressure distributions for the trailing-edge control, first with a control deflection of 16° and an angle of attack of 0° and second with an angle of attack of 16° and a control deflection of 0° . The prediction of the angle-of-attack effect is very good; however, the prediction of the control-deflection effect is poor. On the wing lower surface, the flow separates ahead of the hinge line and then gradually increases in pressure to the trailing edge. The effects on the hinge moment of the discrepancies between experimental and theoretical pressure distributions are of a compensating nature and therefore the experimental loss in hinge moment is considerably less than the experimental loss in lift. A similar investigation of the flow details for the tip-control case is needed to understand better the validity of the theoretical predictions at this Mach number.

To study more closely the effect of changes in tip-control hinge-line location and plan form at lower Mach numbers, extensive tests have been made in the Langley 4- by 4-foot supersonic pressure tunnel (ref. 13) and in the Langley 9- by 12-inch supersonic blowdown tunnel (refs. 29 and 30 and unpublished data). The correlation of the hinge-moment-slope parameters with area ratio at a Mach number of 1.6 for the 10 configurations tested is presented in figure 11. From this figure it is evident that the slope parameters correlate satisfactorily with area ratio, despite the secondary effects of plan form, which cause some scatter of the points. The tip controls may be balanced at this condition for an area ratio near 0.4, and the ratio for balancing $C_{h\delta}$ is very close to the ratio necessary to balance $C_{h\alpha}$.

The balancing of control hinge moments at a control deflection of 0° and an angle of attack of 0° is likely, however, to prove misleading in view of the effect of angle of attack and control deflection. The most closely balanced controls tend to have the most nonlinear hinge-moment characteristics. Figure 12 shows the hinge-moment-coefficient curves with control deflection at several angles of attack for a 55-percent-balanced control at a Mach number of 1.61. As the angle of attack is

~~CONFIDENTIAL~~

~~CONFIDENTIAL~~

NACA RM L53I17a

increased to 12° , the curves become increasingly nonlinear and in some regions the control is overbalanced. On the right-hand side of the figure, the hinge-moment curves for a control having less balance show an increased slope but no regions of overbalance with control deflection. In an attempt to reduce the nonlinearities, a fence was installed at the wing-control parting line to prevent crossflow through the angular gap due to deflection of the control (ref. 34). When this fence was installed, the average effect was an improvement in the linearity of the curves. A similar linearizing effect of the fence was also found in tip- and horn-balanced-control tests in the Langley 9- by 12-inch supersonic blowdown tunnel (refs. 30 and 14).

Other balancing devices which have been tested, but which are not discussed in detail here, are the paddle balances, tabs, and all-movable controls. The paddle balances (ref. 5) are very effective at supersonic speeds in reducing $C_{h\delta}$ and can be used alone to reduce $C_{h\alpha}$; however, there is a very large drag penalty associated with their use. Tabs (refs. 33 and 34) are less effective at supersonic speeds than at subsonic speeds in balancing the hinge moments and require large deflections. All-movable delta controls appear encouraging at supersonic speeds because there is very little shift of the center of pressure with body angle of attack or wing deflection; however, there is a large shift in center of pressure through the transonic speed range and the method of mounting poses considerable problems.

CONCLUSIONS

Correlations have been obtained, on the basis of simple geometric parameters, which permit quick estimates of the effectiveness and hinge-moment characteristics of controls of any plan form or location on wings of many plan forms at supersonic speeds. Closely balanced controls tend to exhibit nonlinear hinge-moment characteristics with control deflection and angle of attack. On tip and horn-balanced controls, a fence installed at the wing-control parting line produces a linearizing effect.

Langley Aeronautical Laboratory,
National Advisory Committee for Aeronautics,
Langley Field, Va., September 1, 1953.

~~CONFIDENTIAL~~

REFERENCES AND BIBLIOGRAPHY

Control Effectiveness

1. Mitchell, Meade H., Jr.: Effects of Varying the Size and Location of Trailing-Edge Flap-Type Controls on the Aerodynamic Characteristics of an Unswept Wing at a Mach Number of 1.9. NACA RM L50F08, 1950.
2. Jacobsen, Carl R.: Effects on Control Effectiveness of Systematically Varying the Size and Location of Trailing-Edge Flaps on a 45° Sweptback Wing at a Mach Number of 1.9. NACA RM L51I26, 1951.
3. Schult, Eugene D., Strass, H. Kurt, and Fields, E. M.: Free-Flight Measurements of Some Effects of Aileron Span, Chord, and Deflection and of Wing Flexibility on the Rolling Effectiveness of Ailerons on Sweptback Wings at Mach Numbers Between 0.8 and 1.6. NACA RM L51K16, 1952.
4. Strass, H. Kurt, Fields, E. M., and Schult, Eugene D.: Some Effects of Spanwise Aileron Location and Wing Structural Rigidity on the Rolling Effectiveness of 0.3-Chord Flap-Type Ailerons on a Tapered Wing Having 63° Sweepback at the Leading Edge and NACA 64A005 Airfoil Sections. NACA RM L51D18a, 1951.

Hinge Moments

Overhang-nose-balanced controls:

5. Boyd, John W., and Pfyl, Frank A.: Experimental Investigation of Aerodynamically Balanced Trailing-Edge Control Surfaces on an Aspect Ratio 2 Triangular Wing at Subsonic and Supersonic Speeds. NACA RM A52L04, 1953.
6. Thomas, G. B.: Analysis of Supersonic Wind-Tunnel Tests of Balanced Aileron Configurations for the Nike Guided Missile. Rep. No. SM-13796, Douglas Aircraft Co., Inc., Sept. 29, 1950.
7. Wiley, Harleth G.: Aerodynamic Characteristics at Transonic Speeds of a 60° Delta Wing Equipped With a Triangular Plan-Form Control Having a Skewed Hinge Axis and an Overhang Balance. Transonic-Bump Method. NACA RM L50L01, 1951.
8. Mueller, James N., and Czarnecki, K. R.: Preliminary Data at a Mach Number of 2.40 of the Characteristics of Flap-Type Controls Equipped With Plain Overhang Balances. NACA RM L52F10, 1952.

~~CONFIDENTIAL~~

9. Mason, Maxwell, and Miller, Robert C.: Wind-Tunnel Test of 11 Per Cent Scale Semispan Models of the Douglas Nike 484 Missile. Rep. No. SWT 12-8, Jet Propulsion Lab., C.I.T., 1950.
10. Lockwood, Vernard E., and Hagerman, John R.: Aerodynamic Characteristics at Transonic Speeds of a Tapered 45° Sweptback Wing of Aspect Ratio 3 Having a Full-Span Flap Type of Control With Overhang Balance. Transonic-Bump Method. NACA RM L51111, 1952.
11. Thompson, Robert F., and Moseley, William C., Jr.: Hinge-Moment and Control-Effectiveness Characteristics of an Outboard Flap With an Overhang Nose Balance on a Tapered 35° Sweptback Wing of Aspect Ratio 4. Transonic-Bump Method. NACA RM L52G08, 1952.
12. Groom, Delwin R., and Wiley, Harleth G.: Investigation of Transonic Speeds of the Hinge-Moment and Lift-Effectiveness Characteristics of a Single Flap and a Tandem Flap on a 60° Delta Wing. NACA RM L53E28a, 1953.

Horn-balanced controls:

References 5, 6, and 9.

13. Czarnecki, K. R., and Lord, Douglas R.: Hinge-Moment Characteristics for Several Tip Controls on a 60° Sweptback Delta Wing at Mach Number 1.61. NACA RM L52K28, 1953.
14. Guy, Lawrence D.: Control Hinge-Moment and Effectiveness Characteristics of a Horn-Balanced, Flap-Type Control on a 55° Sweptback Triangular Wing of Aspect Ratio 3.5 at Mach Numbers of 1.41, 1.62, and 1.96. NACA RM L52L15, 1953.
15. Wiley, Harleth G., and Zontek, Leon: Aerodynamic Characteristics at Transonic Speeds of a 60° Delta Wing Equipped With a Constant-Chord Flap-Type Control With and Without an Unshielded Horn Balance. Transonic-Bump Method. NACA RM L51H22, 1952.
16. Thomas, G. B.: Analysis of Additional Supersonic Wind-Tunnel Tests of Balanced Aileron Configurations for the Nike Guided Missile. Rep. No. SM-14290, Douglas Aircraft Co., Inc., Mar. 14, 1952.
17. Mitcham, Grady L., Crabill, Norman L., and Stevens, Joseph E.: Flight Determination of the Drag and Longitudinal Stability and Control Characteristics of a Rocket-Powered Model of a 60° Delta-Wing Airplane From Mach Numbers of 0.75 to 1.70. NACA RM L51I04, 1951.

~~CONFIDENTIAL~~

~~CONFIDENTIAL~~

18. Mitcham, Grady L., Stevens, Joseph E., and Norris, Harry P.: Aerodynamic Characteristics and Flying Qualities of a Tailless Triangular-Wing Airplane Configuration As Obtained From Flights of Rocket-Propelled Models at Transonic and Low Supersonic Speeds. NACA RM L9107, 1950.

Unbalanced controls:

References 5, 6, 9, 13, 15, and 16.

19. Boyd, John W.: Aerodynamic Characteristics of Two 25-Percent-Area Trailing-Edge Flaps on an Aspect Ratio 2 Triangular Wing at Subsonic and Supersonic Speeds. NACA RM A52D01c, 1952.
20. Czarnecki, K. R., and Mueller, James N.: Investigation at Mach Number 1.62 of the Pressure Distribution Over a Rectangular Wing With Symmetrical Circular-Arc Section and 30-Percent-Chord Trailing-Edge Flap. NACA RM L9J05, 1950.
21. Czarnecki, K. R., and Mueller, James N.: Investigation at Supersonic Speeds of Some of the Factors Affecting the Flow Over a Rectangular Wing With Symmetrical Circular-Arc Section and 30-Percent-Chord Trailing-Edge Flap. NACA RM L50J18, 1951.
22. Ulmann, Edward F., and Lord, Douglas R.: An Investigation of Flow Characteristics at Mach Number 4.04 Over 6- and 9-Percent-Thick Symmetrical Circular-Arc Airfoils Having 30-Percent-Chord Trailing-Edge Flaps. NACA RM L51D30, 1951.
23. Dunning, Robert W., and Ulmann, Edward F.: Aerodynamic Characteristics at Mach Number of 4.04 of a Rectangular Wing of Aspect Ratio 1.33 Having a 6-Percent-Thick Circular-Arc Profile and a 30-Percent-Chord Full-Span Trailing-Edge Flap. NACA RM L53D03, 1953.
24. Kolbe, Carl D., and Tinling, Bruce E.: Tests of a Triangular Wing of Aspect Ratio 2 in the Ames 12-Foot Pressure Wind Tunnel. III - The Effectiveness and Hinge Moments of a Skewed Wing-Tip Flap. NACA RM A8E21, 1948.
25. Sivells, James C., and Goin, Kenneth L.: Experimental and Calculated Hinge Moments of Two Ailerons on a 42.7° Sweptback Wing at a Mach Number of 1.9. NACA RM L8K24a, 1949.
26. Boatright, William B., and Rainey, Robert W.: Hinge-Moment Measurements of a Wing With Leading-Edge and Trailing-Edge Flaps at a Mach Number of 1.93. NACA RM L8K12a, 1949.

~~CONFIDENTIAL~~

~~CONFIDENTIAL~~

27. Conner, D. William, and Mitchell, Meade H., Jr.: Control Effectiveness and Hinge-Moment Measurements at a Mach Number of 1.9 of a Nose-Flap and Trailing-Edge Flap on a Highly Tapered Low-Aspect-Ratio Wing. NACA RM L8K17a, 1949.

Balanced tip controls:

References 13 and 16.

28. Martz, C. William, Church, James D., and Goslee, John W.: Rocket-Model Investigation To Determine the Force and Hinge-Moment Characteristics of a Half-Delta Tip Control on a 59° Sweptback Delta Wing Between Mach Numbers of 0.55 and 1.43. NACA RM L52H06, 1952.
29. Conner, D. William, and May, Ellery B., Jr.: Control Effectiveness Load and Hinge-Moment Characteristics of a Tip Control Surface on a Delta Wing at a Mach Number of 1.9. NACA RM L9H05, 1949.
30. Guy, Lawrence D.: Control Hinge-Moment and Effectiveness Characteristics of a 60° Half-Delta Tip Control on a 60° Delta Wing at Mach Numbers of 1.41 and 1.96. NACA RM L52H13, 1952.
31. Conner, D. William, and May, Ellery B., Jr.: Control Effectiveness and Hinge-Moment Characteristics of a Tip Control Surface on a Low-Aspect-Ratio Pointed Wing at a Mach Number of 1.9. NACA RM L9H26, 1949.
32. Wingrove, A. A., and Pindar, A. C. S.: Tests in High Speed Wind Tunnel on Half-Model of Delta Wing With Moving Tip Control. TN No. Aero. 2052, British R.A.E., May 1950.

Paddle balances:

Reference 5.

Tab balances:

Reference 5.

33. Lockwood, Vernard E., and Fikes, Joseph E.: Preliminary Investigation at Transonic Speeds of the Effect of Balancing Tabs on the Hinge-Moment and Other Aerodynamic Characteristics of a Full-Span Flap on a Tapered 45° Sweptback Wing of Aspect Ratio 3. NACA RM L52A23, 1952.

~~CONFIDENTIAL~~

34. Czarnecki, K. R., and Lord, Douglas R.: Preliminary Investigation of the Effect of Fences and Balancing Tabs on the Hinge-Moment Characteristics of a Tip Control on a 60° Delta Wing at Mach Number 1.61. NACA RM L53D14, 1953.

35. Wegener: Preliminary Results of the Wind Tunnel Development of Control Surfaces With Tabs for the Control of the Wasserfall Device. Douglas Aircraft Co., Inc. translation of Archiv. No. 66/153, Wasserbau Exp. Inst. (Munich), Oct. 31, 1944.

All-movable controls:

36. Conner, D. William: Aerodynamic Characteristics of Two All-Movable Wings Tested in the Presence of a Fuselage at a Mach Number of 1.9. NACA RM L8H04, 1948.

37. Johnson, M. C.: Wing Panel Hinge Moments for the Sparrow I Missile at a 45° Bank Angle. Rep. No. SM-14560, Douglas Aircraft Co., Inc., Jan. 8, 1953.

38. Johnson, M. C.: Analysis of Wing Panel Normal Force and Hinge Moment Characteristics From Wind Tunnel Tests of a 45-Percent-Scale Model of the Sparrow I Missile at Mach Numbers of 1.4 and 1.9. Rep. No. SM-14552, Douglas Aircraft Co., Inc., Jan. 16, 1953.

Fences:

References 14, 29, 30, and 34.

Theory:

Reference 34.

39. Lagerstrom, P. A., and Graham, Martha E.: Linearized Theory of Supersonic Control Surfaces. Jour. Aero. Sci., vol. 16, no. 1, Jan. 1949, pp. 31-34.

40. Goin, Kenneth L.: Equations and Charts for the Rapid Estimation of Hinge-Moment and Effectiveness Parameters for Trailing-Edge Controls Having Leading and Trailing Edges Swept Ahead of the Mach Lines. NACA Rep. 1041, 1951. (Supersedes NACA TN 2221.)

41. Frick, Charles W., Jr.: Application of the Linearized Theory of Supersonic Flow to the Estimation of Control-Surface Characteristics. NACA TN 1554, 1948.

42. Coale, Charles W.: Supersonic Characteristics of Rectangular Horn Balanced Ailerons. Rep. No. SM-13718, Douglas Aircraft Co., Inc., Mar. 31, 1950.

43. Tucker, Warren A., and Nelson, Robert L.: Theoretical Characteristics in Supersonic Flow of Two Types of Control Surfaces on Triangular Wings. NACA Rep. 939, 1949. (Supersedes NACA TN's 1600, 1601, and 1660.)
44. Kainer, Julian H., and King, Mary Dowd: The Theoretical Characteristics of Triangular-Tip Control Surfaces at Supersonic Speeds. Mach Lines Behind Trailing Edges. NACA TN 2715, 1952.
45. Kainer, Julian H., and Marte, Jack E.: Theoretical Supersonic Characteristics of Inboard Trailing-Edge Flaps Having Arbitrary Sweep and Taper. Mach Lines Behind Flap Leading and Trailing Edges. NACA TN 2205, 1950.
46. Goin, Kenneth L.: Theoretical Analyses To Determine Unbalanced Trailing-Edge Controls Having Minimum Hinge Moments Due to Deflection at Supersonic Speeds. NACA RM L51F19, 1952.
47. Morrisette, Robert R., and Oborny, Lester F.: Theoretical Characteristics of Two-Dimensional Supersonic Control Surfaces. NACA TN 2486, 1951. (Supersedes NACA RM L8G12.)
48. Tucker, Warren A., and Nelson, Robert L.: Theoretical Characteristics in Supersonic Flow of Constant-Chord Partial-Span Control Surfaces on Rectangular Wings Having Finite Thickness. NACA TN 1708, 1948.

~~CONFIDENTIAL~~




Figure 1




Figure 2

~~CONFIDENTIAL~~

~~CONFIDENTIAL~~

OVERHANG NOSE-BALANCED CONTROLS




Figure 3

EFFECT OF δ AND α




Figure 4

~~CONFIDENTIAL~~

3B

NACA RM L53117a

~~CONFIDENTIAL~~

17




Figure 5




Figure 6

~~CONFIDENTIAL~~

~~CONFIDENTIAL~~




Figure 7




Figure 8

~~CONFIDENTIAL~~

~~CONFIDENTIAL~~

HIGH MACH NUMBER CHARACTERISTICS




Figure 9

HIGH MACH NUMBER PRESSURE DISTRIBUTIONS






Figure 10

~~CONFIDENTIAL~~

~~CONFIDENTIAL~~



HINGE-MOMENT NONLINEARITIES FOR TIP CONTROLS



~~CONFIDENTIAL~~